

PIATRA ONLINE

021 9907 / office@piatraonline.ro

Aleea Teisani nr.137A, sector 1, 014034 Bucuresti

CARACTERISTICI PRODUS: HARDSCAPE PORCELAIN ETNA		CARACTERISTICI TEHNICE	STANDARD	LIMITE STABILITE	HARDSCAPE PORCELAIN®
REGULARITATE		LUNGIME SI LATIME	ISO 10545-2	$\pm 0.6 \%$	CONFORM
		GROSIME	ISO 10545-2	$\pm 5.0 \%$	CONFORMITATE
		RECTANGULARITATE	ISO 10545-2	$\pm 0.6 \%$	CONFORMITATE
		RECTITUDINEA LATURILOR	ISO 10545-2	$\pm 0.5 \%$	CONFORMITATE
		PLANEITATEA SUPRAFETEI	ISO 10545-2	$\pm 0.5 \%$	CONFORMITATE
STRUCTURA		ABSORBȚIA APEI	ISO 10545-3	$\leq 0.5 \%$	CONFORMITATE
		REZISTENTA LA RUPERE	ISO 10545-4	$\geq 1300 \text{ N}$	>10000 N
		MODUL DE RUPERE	ISO 10545-4	$\geq 35 \text{ N/mm}^2$	>35 N/mm ²
		CLASA SARCINII DE RUPERE	EN 1339	VALOARE DECLARATA	U11*
TERMIC HIGROMETRIC		REZISTENTA LA INGHET	ISO 10545-12	TEST REUSIT	GARANTAT
CHIMIC		CONTINUT DE PLUMB ȘI CADMIU	ISO 10545-15	VALOARE DECLARATA	ABSENT
SIGURANTA		REZISTENTA LA ALUNECARE	DIN 51130	VALOARE DECLARATA	R11
SUPRAFATA		REZISTENTA LA ABRAZIUNE	ISO 10545-7	CLASA DECLARATA	CAPPUCCINO CLASA 4
					GRI DESCHIS CLASA 4
					GRI INCHIS CLASA 3

In conformitate cu standardele EN 14411 (ISO 13006) anexa G grup Bla